



Sun Control Window Films

Performance Results on 1/4" Clear:

Visible Light Transmitted	36%
Total Solar Energy Rejected	51%
UV Light Rejected	99.9%
Glare Reduction	59%
Visible Light Reflected Interior	7%
Visible Light Reflected Exterior	13%
Solar Heat Reduction	40%



Night Vision 35

*Enhancing light
as only 3M can*



Night Vision 35 Benefits:

- Great heat rejection provides energy savings and improved comfort
- A warm natural hue invites warmth and beauty to any room
- Extends the life of furnishings by significantly reducing UV rays, the largest cause of fading
- Low interior and exterior reflectivity, especially at night!
- New 3M nano-technology enhances color stability
- Reduces glare and eye discomfort
- Comprehensive 3M manufacturer's warranty
- Increases personal safety from flying glass
- Superior scratch resistant coating

Interior View



The Skin Cancer Foundation recommends many 3M Window Film products as an effective UV protectant.

Performance data generated for a typical film on 6mm glass using applicable industry test methods and standards.

Night Vision 35

*Enhancing light
as only 3M can*




Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	36%	22%	32%	19%
Total Solar Energy Rejected	51%	57%	45%	59%
UV Light Rejected	99.9%	99.9%	99.9%	99.9%
Glare Reduction	59%	58%	60%	60%
Visible Light Reflected Int.	7%	6%	8%	8%
Visible Light Reflected Ext.	13%	8%	19%	10%
Solar Heat Gain Coefficient	0.49	0.43	0.55	0.42
Luminous Efficacy	0.7	0.5	0.6	0.5
U Value	1.03	1.03	0.47	0.47
Solar Heat Reduction	40%	32%	21%	18%



Renewable Energy Division

3M Center, Building 235-2S-27
St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2011 70-0709-0163-5 (211.5)ii



Exterior View

For color and appearance on our sample cards, no UV Protection or Abrasion Coating has been applied.